

Auramix 300



constructive solutions

Advanced low viscosity retarding Superplasticiser, based on Polycarboxylic technology

Uses

Auramix 300 is a high performance retarding superplasticiser intended for applications where retardation and long workability retention are required, and it has been developed for use in:

- Mass raft foundation
- Pumped concrete
- Concrete requiring long workability retention
- High performance concrete

Advantages

- Increased retardation controls the heat of hydration and yields high ultimate strength
- Higher E modulus
- Improved adhesion to reinforcing and prestressing steel
- Better resistance to carbonation
- Lower permeability
- Better resistance to aggressive atmospheric conditions
- Reduced shrinkage and creep
- Increased durability

Description

Auramix 300 is a unique combination of the latest generation superplasticisers, based on a polycarboxylic ether polymer with long lateral chains. This greatly improves cement dispersion. At the start of the mixing process an electrostatic dispersion occurs but the cement particle's capacity to separate and disperse. This mechanism considerably reduces the water demand in flowable concrete.

Auramix 300 combines the properties of water reduction and workability retention. It allows the production of high performance concrete and/or concrete with high workability.

Auramix 300 is a strong superplasticiser allowing production of consistent concrete properties around the required dosage.

Technical support

Fosroc provides a technical advisory service for on-site assistance and advice on mix design, admixture selection, evaluation trials and dispensing equipment.

Properties

Appearance	: Light yellow coloured liquid
pH	: Minimum 6.0
Volumetric mass @ 20°C	: 1.05 kg/litre
Chloride content	: Nil to IS:456
Alkali content	: Typically less than 1.5 g Na ₂ O equivalent / litre of admixture.

Dosage

The optimum dosage of Auramix 300 to meet specific requirements should always be determined by trials using the materials and conditions that will be experienced in use. The normal dosage range is between 0.5 to 3.0 ltrs/100 kg of cementitious material.

Use at other dosages

Dosage outside the normal range quoted above can be used to meet particular mix requirements. Contact Fosroc for advice in these cases

Effects of overdosing

Overdosage may cause delay in the setting time and segregation.

Estimating

Packaging

Auramix 300 is available in 200 litre drums and bulk tanker.

Storage

Auramix 300 has a minimum shelf life of 24 months provided the temperature is kept within the range of 2°C to 50°C. Should the temperature of the product fall outside this range then contact local Fosroc office for advice.

Auramix 300

Precautions

Health and safety instructions

Auramix 300 does not fall into the hazard classifications of current regulations. However, it should not be swallowed or allowed to come into contact with skin and eyes.

Suitable protective gloves and goggles should be worn.

Splashes on the skin should be removed with water. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately - do not induce vomiting.

For further information consult the Material Safety Data sheet available for this product.

Fire

Auramix 300 is water based and non- flammable.

Cleaning and disposal

Spillages of Auramix 300 should be absorbed onto sand, earth or vermiculite and transferred to suitable containers. Remnants should be hosed down with large quantities of water.

The disposal of excess or waste material should be carried out in accordance with local legislation under the guidance of the local waste regulatory authority.

® Denotes the trademark of Fosroc International Limited

Important note :

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.



Fosroc Chemicals (India) Pvt. Ltd. Head Office

'Vishnu Chittam', No. 10, 2nd Floor
Sirur Park B Street, Seshadripuram
Bangalore 560020

www.fosroc.com

telephone	fax	e-mail
++91 80-2356 3188	++91 80-2356 1178	india@fosroc.com

Certified ISO 9001 by



Regional Offices

Bangalore

'Vishnu Chittam', No.10, 1stFloor
Sirur Park B Street, Seshadripuram
Bangalore 560 020
Ph:080-2356 3188
Fax : 080-23560667
email: Bangalore@fosroc.com

Mumbai

208/209, Persepolis
Sector 17, Vashi
Navi Mumbai 400 703
Ph:022-2789 6411/12
Fax: 022 - 2789 6413
email:Mumbai@fosroc.com

Delhi

109-113, 1st Floor, Vikrant Towers
4, Rajendra Place
New Delhi 110 008
Ph:011- 45062000-5
Fax: 011- 45062001
email:Delhi@fosroc.com

Kolkata

P-569, Lake Terrace Extn.
First Floor
Kolkata 700 029
Ph: 033 24650917 / 55343188
Fax: 033-24650891
email:Kolkata@fosroc.com

Ahmedabad : (079) 26762799

Ankleshwar :(02646) 220704/224687

Bellary: 09845891690

Bhubaneshwar : (0674) 2521176

Chennai : (044) 24899949/24853383

Chandigarh : (0172) 2639360

Cochin : (0484) 2347465

Coimbatore : (0422) 2472966

Goa : (0832) 09423058696

Guwahati : (0361) 2462866

Hyderabad : (040) 27662324/27662425

Indore : (0731) 4049339

Jaipur : (0141) 2336103

Lucknow :(0522) 2239044

Nagpur: (0712) 2753510/2563242

Visakhapatnam : (0891) 2564850 / 2707607

INDIA/01-419/B